

Products Specification

GUDY ELECTRONICS LTD.

Tel:86-755-27810525 Fax:86-755-27810505 Email:info@gudycharger.com Http://www.gudycharger.com

SPECIFICATION		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :	3/1/2012 10:40:00 AM			
COMMON/UNITE	DOC. NO:	REV.: 1.0	PAGE: 1 OF 1	

24V 2.8A Lead-Acid Battery-Pack Charger

No.	Item	Unit	Specification	Remark
INPUT				
01	Rating Input Voltage	V ac	100~240Vac 50/60Hz	
02	Input Voltage Range	V ac	90~264Vac	
03	Rating Input Current	A	1.1Arms	INPUT:220V OUTPUT:Full load
04	Rating Input Power	W	90	
OUTPUT				
05	Rating Output Voltage	Vdc	28V	
06	Output voltage range	Vdc	20VDC ~ 30VDC	
07	Suit with Battery type	%	24V 8~12Ah VRLA	
08	Charging current (stage 1)	A	2.8± 0.2@26V	
09	Charging voltage (stage 2)	V	29.4V +-0.2V	
	Floating voltage (stage 3)	V	27.8V+-0.2V	
10	Cut-off current(stage 2→3)	A	<0.40+-0.05A	
11	Typical charging time	Hour	8	
12	Max. output power	W	75	
13	Hold-on time	ms	NC	Input: 220Vac Output: Full load
14	Ripple current	mA	100	Input: 220Vac Output: Full load
15	Charge finish condition		V>29V + I<0.4A	
16	LED color	-	Red: charging Green: finish/idle	
17	Output shorted protection		YES	
	Output reversed protection		YES	
18	Efficiency	%	80%	At max. load
Environment				
19	Operate temperature	°C	-10 ~ +40	Full load & natural convection.
20	Operate humidity	%RH	< +90	Relative humidity, non-condensing.
21	Storage temperature	°C	-40 ~ +70	
22	Storage humidity	%RH	0 ~ +95	Relative humidity, non-condensing.
23	Cooling		Natural convection	
24	Temperature factor	%	--	
25	Vibration resistance		5MM/50HZ/600S	Non-operating condition.
26	Impact resistance		1 meter drop test >= 3 times	Non-operating condition.
Mechanical				
27	Weight	g	650	
28	Size	mm	170X71X51	Casing only
29	Connectors	--	Defined when order	
Safety				
30	Max. temperature rise	°C	< 40 on casing	At any line and Max. Load
31	Safety standards	-	IEC335 UL1310	
32	EMC standard	-	EN55014	
33	MTBF	hrs	30000	
34	Limited power source	VA	-	
35	ESD	kV	8.0	
36	Hi-Pot Insulation	V	i/p to o/p: 3000 (1 min.)	For final unit, cut-off current =10mA