

### 36V 3A lead acid battery charger

<b>SPECIFICATION</b>		<b>PREPARE</b>	<b>CHECK</b>	<b>APPROVE</b>
MODEL:		Rain	Steven	Wilstar
ISSUE DATE:	2008/5/8			
COMMON/UNITE	DOC.NO:		REV: 1.0	PAGE:1 OF 1

#### Smart 3-Stages SLA Battery charger

	ITEM	UNIT	SPECIFICATION	REMARK
<b>INPUT</b>				
01	Rating Input Voltage	V ac	100~240Vac 50-60Hz	
02	Input voltage range	V ac	90~264Vac	
03	Rating Input Current	A	1.2Arms	220Vac
04	Max.input power	W	150W	
<b>OUTPUT</b>				
05	Rating output voltage	V dc	41.7V	
06	Output voltage range	V dc	30 ~ 44.6Vdc	
07	Suit with Battery type		36V 10~30Ah VRLA	
08	Charging current(stage1)	A	3±0.3@36V	
09	Charging voltage(stage2)	V	44.3V+0.3V	
	Floating voltage(stage3)	V	41.4V+0.2V	
10	Cut-off current(stage2→3)	A	<0.3+0.1A	
11	Typical charging time	hour	8	
12	Max.output power	W	110W	
13	Hold-on time	ms	NC	Input:220Vac Output:Full load
14	Ripple current	mA	200	Input:220Vac Output:Full load
15	Charge finish condition		V>44V +I<0.3A	
16	LED color		Red:charging Green:finish/idle	
17	Output protect	-	OCP&OVP&Polarity error protection	
18	Efficiency	%	75%(min)	At max.load
<b>Environment</b>				
19	Operate temperature	℃	0~+40	Full load&natural convection
20	Operate humidity	%RH	20~90	Relative humidity,non-condensing.
21	Storage temperature	℃	-40~+70	
22	Storage humidity	%RH	10~95	Relative humidity,non-condensing.
23	Cooling	-	Natural convection	
24	Temperature factor	%	--	
25	Vibration resistance		5MM/50HZ/600S	Non-operating condition.
26	Impact resistance		1 meter drop test>=3 times	Non-operating condition.
<b>Mechanical</b>				
27	Weight	g	600g	
28	Size	mm	152.5x63.0x45.0	Casing only
29	Connectors	-	Defined when order	
<b>Safety</b>				
30	Max.temperature rise	℃	<40 on casing	At any line and Max.Load
31	Safety standards	-	CE	
32	EMC standard	-	CE	
33	MTBF	hrs	40000	
34	Limited power source	VA	-	
35	ESD	Kv	8.0	
36	Hi-Pot Insulation	v	Input to Output:3000Vac(1 min.)	For final nuit,cut-off current=10mA